



## General

### Weight

- 259 Lbs. assembled
- 419 Lbs. shipping weight

### Doors

- 6, secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .875" aluminum filled gaskets

### Material

- .125" Alumiflex™
- Finish: Painted cream
- RF properties: Non-ferrous

### Vents

- 30 bottom louvers per door
- 26 top louvers – In top cover, under Alumishield™
- One removable filter panel per door
- 26 fixed filter pads in top cover

### Handles

- Stainless steel, padlocking

### Lifting Hooks

- 4, standard

## Racking Specifications

### Rails

- Three sets standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by two R-STRUTS™
- .160" Material (Alumiflex™)

### Spacing

- 19" or 23" Racking available

### Useable Height

- 26.25"

### Useable Depth

- Maximum: 21.5" Minimum: 19.75"

## Inside Clearance - Less Rails

### Height

- 30"

### Width

- 27.625" each compartment

### Depth

- See racking specifications
- Useable depth

## Ratings

### NEMA Class Types available

- Class 250 Type 4X

### Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

## Door Opening Clearance

### Height

- 26.75"

### Width

- 23.625"

## Exterior Cabinet Dimensions

### Main Body

- Height: 30.98"
- Width: 88.5"
- Depth: 25"

### Alumishield™

- Hang down height: 1.75"
- Width: 93.5"
- Depth: 29.5"

### Handles

- Protrude 1.875"

### Total Space Occupied

- Height: 31.605"
- Width: 94.5"
- Depth: 28.75"

	*Section Starting & Ending Points	Vertical Height Per section	Effective Depth For Each Section
Top	26.75" – 30.98"	3.25"	21.50"
	26.57" – 26.75"	.18"	20.50"
	21.00" – 26.57"	5.57"	21.50"
Center	9.00" – 21.00"	12.00"	19.75"
	3.43" – 9.00"	5.57"	21.50"
	3.25" – 3.43"	.18"	20.50"
Bottom	0.00" – 3.25"	3.25"	21.50"