



Picture shown are examples only : See details for specifications



General

***Approximate Weight**

- 390 Lbs. assembled
- 540 Lbs. shipping weight

Doors

- 4, secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with .3/8" aluminum filled gaskets

Material

- .125" Alumiflex™
- Finish: Painted cream
- RF properties: Non-ferrous

Vents

- 30 bottom louvers per door
- 20 top louvers – In top cover, under Alumishield™
- One removable filter panel per door
- 20 fixed filter pads in top cover

Handles

- Zinc Die Powder-coated Black EMKA Three Point Padlocking Handles

Lifting Hooks

- 6, standard

Racking Specifications

Rails

- Four sets standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by three R-STRUTS™
- .125" Material (Alumiflex™)

Spacing

- 19" or 23" Racking standard

Inside Clearance - Less Rails

Height

- 49.98"

Width

- 27.625" each side

Depth

- 27.75"

Ratings

NEMA Class Types available

- NEMA 3R (Vented), NEMA 4 (closed loop-a/c) , NEMA 4X

Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

Door Opening Clearance

Height

- 46"

Width

- 23.5"

Exterior Cabinet Dimensions

Main Body

- Height: 50.23"
- Width: 59"
- Depth: 34"

Alumishield™

- Hang down height: 1.71"
- Width: 61.96"
- Depth: 36.67"

Handles

- Protrude 2.2"

Total Space Occupied

- Height: 50.855"
- Width: 65"
- Depth: 38.4"

	*Section Starting & Ending Points	Vertical Height Per section	Effective Depth For Each Section
Top	46.75" – 50.23"	3.25"	30.50"
	46.57" – 46.75"	.18"	29.50"
	31.00"- 46.57"	15.57"	30.50"
Center	19.00"-31.00"	12.00"	28.75"
	3.43" – 19.00"	15.57"	30.50"
	3.25" – 3.43"	.18"	29.50"
Bottom	0.00" – 3.25"	3.25"	30.50"