



\*\*\*Picture shown are examples only : See details for specifications\*\*\*



## General

### \*Approximate Weight

- 555 Lbs. assembled
- 705 Lbs. shipping weight

### Doors

- 4, secured by three point locking system
- Locks via customer supplied padlocks
- Sealed with 3/8" aluminum filled gaskets
- 4 Auto door stops standard

### Material

- .125" Alumiflex™
- Finish: Painted cream
- RF properties: Non-ferrous

### Vents

- 30 bottom louvers per door
- 20 top louvers – In top cover, under Alumishield™
- One removable filter panel per door
- 20 fixed filter pads in top cover

### Handles

Zinc Die Powder-coated Black EMKA Three Point Padlocking Handles

### Lifting Hooks

- 8, standard

## Racking Specifications

### Rails

- Four sets standard (for additional rails see accessories)
- Alodine coated
- Holes tapped for 10-32 threads
- Each rail supported by three R-STRUTS™
- .125" Material (Alumiflex™)

### Spacing

- 19" or 23" Racking standard

## Inside Clearance - Less Rails

### Height

- 77.98"

### Width

- 27.625" each side

### Depth

- 35.75"

## Ratings

### NEMA Class Types available

- NEMA 3R (Vented), NEMA 4 (closed loop-a/c), NEMA 4X

### Paint Tested

- 1000 Hour salt spray (textured)
- 1000 Hour immersion

## Door Opening Clearance

### Height

- 74"

### Width

- 23.5"

## Exterior Cabinet Dimensions

### Main Body

- Height: 78.23"
- Width: 59"
- Depth: 42"

### Alumishield™

- Hang down height: 1.71"
- Width: 61.96"
- Depth: 44.67"

### Handles

- Protrude 2.2"

### Total Space Occupied

- Height: 78.85"
- Width: 65"
- Depth: 46.4"

	*Section Starting & Ending Points	Vertical Height Per section	Effective Depth For Each Section
Top	74.75" – 78.23"	3.25"	38.50"
	74.57" – 74.75"	.18"	37.50"
	45.00" – 74.57"	29.57"	38.50"
Center	33.00" – 45.00"	12.00"	36.75"
	3.43" – 33.00"	29.57"	38.50"
	3.25" – 3.43"	.18"	37.50"
Bottom	0.00" – 3.25"	3.25"	38.50"